

**PRODUCT DATASHEET**  
**GLOBAL TAG F-WRISTBY**



Global Tag **F-WRISTBY** is a RFID/NFC wristband, composed of a PVC mini-card (reusable) and a disposable fabric band.


**F-WRISTBY** is available in LF and HF (also NFC) bands, with many different customizations like the choice of the background color or the complete customized printing.

The RFID wristband F-Wristby is one of the most used tags for festival micropayments, camping, SPA and resort entrance, and museum ticketing.



**MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS**

PVC mini-card available dimensions:




Card size: 42x26mm  
Hole size: 3x20mm



Card size: 40x25mm  
Hole size: 3x15mm



Card size: 39x25mm  
Hole size: 2x18mm



Card size: 34.5x26mm  
Hole size: 3.9mm



Card size: 35x26mm  
Hole size: 2x15mm



Card size: 50.8x25.4mm  
Hole size: 2x15mm



Card size: 33x26mm  
Hole size: 2x15mm




Card size: 38x20mm  
Hole size: 2x15mm



Card size: 50.8x28mm  
Hole size: 2x15mm

Strap available dimensions:





**Material:** Mini card: PVC; Strap: fabric

**Color:** To be customized

**Class Protection:** IP68 (Totally protected against ingress of solid / Protected against long period of immersion)

**Storage Temperature:** -55°C + 65°C / -67°F to +149°F

**Operating Temperature:** -25°C + 50°C / -13°F to +122°F

**Weather Ability:** Very Good, including UV resistance and sea water

**Delivery format:** Individual

**Expected lifetime:** Years in normal operating conditions

### CHIP SPECIFICATION AVAILABLE

	LF 125Khz	HF 13,56MHz
Device type	N.D.	N.D.
Air interface protocol	N.D.	ISO14443 and ISO15693 and <b>NFC</b>
IC Type Available	TK4100, T5577, EM4200, other on request	I-Code SLIX, I-Code SLIS, Mifare Ultralight, Mifare Classic 1K, Mifare Classic 4K, Mifare Plus X 4K, Mifare Desfire 4K, STM LRI2k, Ntag213, Ntag216 other on-request
Size Inlay	18mm diameter	18mm diameter
Read Range	From 2 to 10cm	From 2 to 20cm

### CUSTOMIZATION OPTIONS

**Silk Printing :** 4-colors printing logo

**Pre-Encoding:** Customer specific encoding of EPC or User Memory (also from Database). Locking permanently or with password. Insert into Database TID code. For NFC chip encoding memory with different type of NFC (E-mail, URI etc.)

### APPLICATION NOTE

**Access Control:** **F-WRISTBY** is used for access control in many different environment as swimming-pool, aquatic park, SPA or beauty center, hotel.

**Micro-Payment and ticketing:** **F-WRISTBY**, in particular with HF ISO14443 (NFC) chip, can be used for micro-payment in events like festival.

**Fidelity or VIP Pass**

### ORDER INFORMATION

**PRODUCT CODE:** GT-F\_WRSTY-xx (xx defined type of chip required)

On demand we can also produce transponder with different color or with other type of customization... contact us for more information:

**Global Tag Srl** – Via Zanardelli 13/A 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W [www.global-tag.com](http://www.global-tag.com)

M [sales@global-tag.com](mailto:sales@global-tag.com)



## **DISCLAIMER**

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document. Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application. Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2024- Global Tag Srl