

PRODUCT DATASHEET

GLOBAL TAG **WALL-MOUNT BEACONY (BLE)**



BLUETOOTH
LOW ENERGY

NEW PRODUCT

CE

RoHS
Compliant

Global Tag **WALL-MOUNT BEACONY** is a BLE (Bluetooth Low Energy 4.2) **Smart Beacon** based on Disk Beacony, with silicone keyfob housing. It can be used for asset tracking and maintenance.

- Waterproof silicone housing
- ON/OFF button with additional functions (reset, alarm)
- Battery CR2032 replaceable
- Press-fit housing closure
- Up to 200m detection distance
- iBeacon and Eddystone (UID, URL, TLM) compliant
- Sticker with Mac Address (and its QRcode) and Friendly Name on the beacon surface
- Optionally, **accelerometer, temperature/humidity sensor**
- Optionally, **NFC** integrated
- Choice between a wide range of Firmwares

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions: 75x35mm / 2,95x1,37 inches

Thickness: 12mm / 0,47 inches

Weight: 17,5gr.

Material: Silicone (external case) – Polycarbonate (internal case)

Color: White (Customized on request).

Class Protection: IP67

Battery type: CR2032 replaceable (Panasonic®).

Battery life: One year (with Broadcast Interval: 1 second and Tx Power: 0dB)

System-On-Chip (SoC): Nordic NRF 52810

Storage Temperature: -15°C to +50°C / 5°F to +122°F

Operating Temperature: -15°C to +45°C / 5°F to +113°F

Delivery format: Singulated

Expected lifetime: Years in normal operating conditions

G-Sensor: ST Microelectronics mod. LIS3DH

Temperature/Humidity Sensor: Sensirion mod. SHT3x-DIS



ELECTRONIC AND OPERATIVE PARAMETERS

Operation Frequency: 2400-2483,5MHz

IEEE Standard: 802.15.1 (Bluetooth 4.2 Low Energy BLE)

Transmission distance: up to 200meters

Transmission Power: 4 different Level (-23dBm / -6dBm / 0dBm / +4dBm)

Default Ping Rate: 1s

Ping Rate interval: 100ms to 10000ms. (step of 100ms) – Except optional “longer broadcast interval FW”

Support Operating System: iOS7.0 and Android 4.2+

Scan Response: Yes (max 31Byte Length), containing Battery level, Device name (11Byte), Sensors value

FCC and CE Certification

CUSTOMIZATION OPTIONS

Housing Printing : Logo printing or serial number laser engraving

Label on surface: Label can be customized according to customer’s request

Setting / Encoding: Beacons services values can be pre-set as per customer’s requirement (from xls file)

Available sensors: Accelerometer and/or temperature/humidity sensor

Firmware: Different FW are available, which can be uploaded on request

INSTALLATION MODE

Rivets: Wall-Mount Beacons can be mounted with screws or rivets, thanks to the lateral holes of the tag.

APPLICATION NOTE

Asset Tracking

Maintenance

Indoor/Outdoor Positioning

PRODUCT CODE AND ORDER INFORMATION

GT-WLBY-BLE: Wall Mount Beacons without sensors

GT-WLBY_A-BLE: Wall Mount Beacons with **accelerometer**

GT-WLBY_TH_BLE: Wall Mount Beacons with **temperature/humidity sensor**

GT-WLBY_ATH-BLE: Wall Mount Beacons with **accelerometer** and with **temperature/humidity sensor**

For any clarification, please do not hesitate to contact us at any time:

Global Tag Srl – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2019 - Global Tag Srl