PRODUCT DATASHEET

GLOBAL TAG UHF 7012





Global Tag **UHF 7012** is a RFID UHF antenna design which has been designed to offer high performance, despite a reasonable dimension. Size of this antenna design is 70x12mm.

This RFID tag enables a long reading distance, thanks to its antenna design. The suggested applications fields are RFID waste management, retail, cloths inventory, logistic management.

Different customizations are available such as die-cut label size, encoding of EPC/memory, or content printing.







MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Antenna Size: 70x12mm Wet inlay size: 73x15mm

Paper/PP/PET label size: 73x15mm

Pitch Size: 20mm Gap: 5mm

Web Width: 76mm

Mounting System: Glue, (optionally 3M 467 adhesive or Removable Glue)

Material: Dry-inlay, Wet-inlay, Paper, PP or PET

Antenna Material: Aluminum

 $\label{thm:continuous} \textbf{Storage Temperature:} +10^{\circ}\text{C to } +35^{\circ}\text{C (sealed in the vacuum bag and avoid direct sunlight exposure)} \\ \textbf{Storage Humidity:} 30\% to 70\% RH (sealed in the vacuum bag and avoid direct sunlight exposure)} \\$

After gluing Temperature: -20°C to +50°C After gluing Humidity: 20% to +80% RH

Delivery format: in reel

73±0.2mm 73±0.2mm 73±0.5mm 1.5±0.5mm 1.5±0.5mm 1.5±0.5mm 1.5±0.5mm 1.5±0.5mm 1.5±0.5mm 1.5±0.5mm

IC CHIP SPECIFICATION

Operation Frequency	UHF 860-960 MHz
Air interface protocol	UHF EPC Class 1 Gen 2
IC Type Available	NXP U-Code 8
TID Memory	96bit
EPC Memory	128bit
User Memory	-

READING DISTANCE

With long range fixed reader: ---- EU frequency 0 ~ 10m (2W ERP) ----- US frequency 0 ~ 11m (4W EIRP)

INSTALLATION MODE

With permanent strong glue: when mounting the tag with adhesive background, clean and dry the surface to obtain the maximum bond strength. The range temperature must be +10°C to +40°C and humidity range 20% to +80% RH



CUSTOMIZATION OPTIONS

Printing: 4-color or monochrome logo, Progressive number, Serial number from database, Barcode or QRCode.

Encoding: Writing contents in EPC/User Memory (optionally from customer's database)

3M glue: According to the project requirement and basing on the surface material we can supply special adhesive

_ ORDER INFORMATION

Standard products have these available size PRODUCT CODE WET-INLAY: GT-WT7315-U8 PRODUCT CODE PAPER LABEL: GT-PL7315-U8 PRODUCT CODE PET LABEL: GT-PET7315-U8

For further information or customization request:

Global Tag Srl – Via Zanardelli 13/A 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general-purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2024 - Global Tag Srl